

V70 TREE DISC MULCHER

Available width 60"

Efficiently mulch 6-8" diameter trees and quickly cut up to 14" diameter trees.



Do not operate mulcher without a shatterproof cab door on loader.


14.0" CUT CAPACITY	60" CUT WIDTH	30-45 GPM HIGH FLOW PISTON MOTOR	900 LB DISC WEIGHT	2710 LB OVERALL WEIGHT
------------------------------	-------------------------	---	------------------------------	----------------------------------

CHOOSE INTAKE CHUTE:




STANDARD CHUTE

- Tapered design helps guide trees into the disc.
- Bottom edge drops below bottom of disc to scoop trees.



OPEN CHUTE

- Increased space between chute and mulching disc to process larger, bushy material.
- Bottom edge flush with disc, allowing work at or below grade.



REPLACEMENT TOOTH KITS AVAILABLE

- Full kits, partial kits, and individual replacement teeth.
- Includes all required hardware.

Carbide Tooth Steel Tooth



1. BENT-AXIS PISTON MOTOR WITH RELIEF VALVES
2. STANDARD MOTOR GUARD & SPINDLE GUARD
3. 60" FULLY-MACHINED PERFECTLY BALANCED QUADCO® DISC
4. BOLT-ON TOOTH MOUNTS WITH FOUR-SIDED ROTATABLE & REPLACEABLE STEEL TEETH
5. 3 DECK MOUNTED TEETH & RECUTTER BAR FOR A FINER FINISH
6. 3/8" GRADE 80 INTERIOR DECK WELDMENT
7. REPLACEABLE PUSH BAR, CHUTE & DEFLECTOR
8. TWO CHUTE STYLES
Choose from two chute styles; standard or open.
See previous page for details.

MODEL	TDM60
Cut Width (in.)	60.0
Overall Width (in.)	70.0
Overall Height (in.)	40.5
Overall Depth (in.)	77.5
Deck Height (in.)	11.0
Push Bar Height (in.)	40.5
Minimum Cut Height (in.)	2.1
Cutting Capacity, Diameter (in.)	14.0
Number of Teeth: Top / Bottom / Outside	12 / 20 / 12
Maximum Disc Thickness (in.)	1.25
Deck Thickness: Top / Side / Inside (in.)	0.25 / 0.375
Recommended Flow Rate (GPM)	30 - 45 High Flow Only
Approximate Weight (lbs)	2710
Recommended Loader Capacity	Greater than 2800 lbs